


DATALUX.AC

FIXTURES: AC

- Continues light with unsurpassed uniformity.
- Virtually no shading on the workshop floor.
- Polycarbonate housing, UV stabilized, extra clear.
- With internal driver.
- Dust and splashproof (IP65) with a high impact resistance (IK10 rated).
- DATALUX light lines can easily be integrated into building management systems with Dali or other protocols via the 0-10 V connection at the start of the light line.
- Expected LED lifespan: Up to 100,000 hours possible.
- The DATALUX AC fixture has 2 extra power cables as standard for the DCEM emergency lighting TRONIC.



Features

Dimming	0-10 V - 0-100%
Emergency lighting function	With DCEM TRONIC
Ambient temperature range	-20 °C - +40 °C

Mechanical

Dimensions 3 meter	Ø40 mm x 3013 mm (3000 mm pitch)
Dimensions 2 meter	Ø40 mm x 2038 mm (2025 mm pitch)
Weight	3,0 kg / 2,2 kg
IP class	IP65
Housing material	Polycarbonate (UV stabilized)

Electrical


Input voltage	200 - 250 V _{AC}
Fixture efficacy	121 - 144 lm/W
Transitcable AC	2,5 mm ²



DATA LUX.AC

FIXTURES: AC

- Continues light with unsurpassed uniformity.
- Virtually no shading on the workshop floor.
- Polycarbonate housing, UV stabilized, extra clear.
- With internal driver.
- Dust and splashproof (IP65) with a high impact resistance (IK10 rated).
- DATA LUX light lines can easily be integrated into building management systems with Dali or other protocols via the 0-10 V connection at the start of the light line.
- Expected LED lifespan: Up to 100,000 hours possible.
- The DATA LUX AC fixture has 2 extra power cables as standard for the DCEM emergency lighting TRONIC.



2 M

	29,8	45,3	Watt
LUM-DL20AC-NAXX-05K0C	3890 lm*		131 lm/W
LUM-DL20AC-WAXX-05K0C	4130 lm*		139 lm/W
LUM-DL20AC-UWXX-05K0C	3780 lm*		127 lm/W
LUM-DL20AC-NAXX-08K0C		5620 lm*	124 lm/W
LUM-DL20AC-WAXX-08K0C		5990 lm*	132 lm/W
**LUM-DL20AC-UWXX-08K0C		5470 lm*	121 lm/W


* Per 2 meter

3 M


	29,5	44,6	Watt
LUM-DL30AC-NAXX-03K5C	3940 lm*		149 lm/W
LUM-DL30AC-WAXX-03K5C	4170 lm*		149 lm/W
LUM-DL30AC-UWXX-03K5C	3820 lm*		154 lm/W
LUM-DL30AC-NAXX-05K0C		5750 lm*	153 lm/W
LUM-DL30AC-WAXX-05K0C		6120 lm*	150 lm/W
LUM-DL30AC-UWXX-05K0C		5590 lm*	145 lm/W

* Per 3 meter

LUM-DLX0AC-XXXX-XXXXC



2 meter | DL20AC



3 meter | DL30AC

